

Product name : **PETRELAB® 550-Q**
 Code: **77767**

Date of issue: 21/12/2018
 Version: 4

Section 1. Identification

GHS product identifier : PETRELAB® 550-Q
Chemical name : Benzene, C10-13-alkyl derivs.
Other means of identification : Linear alkylbenzene containing side alkyl chains of 10-12 carbon atoms, averaging 11.2 atoms.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses
See specific uses
Specific uses
Use as an intermediate. Preparation of plasticizers. Sealants and adhesives Use in Lubricants. Metalworking-fluid preservatives Manufacture of basic metals, including alloys Coatings and paints, thinners, paint removers Manufacture of paper products. Manufacture of pharmaceutical products. Use as an additive in plastics and rubber. Textile industry Inks and toners Industrial cleaners. Electrical insulation.

Supplier's details : CEPSA Química Bécancour Inc.
 5250 Bécancour Boulevard
 Bécancour (Québec) G9H 3X3
 CANADA

Telephone number : +34 913 376 000

Information limitations : 07:30 - 19:30 (CET)

Email : tuteladeproducto@cepsa.com / productstewardship@cepsa.com

Emergency telephone number :

+44 1865 407333 (Europe, English)	+44 1235 239670 (Europe, multiple languages)
+34 91 114 2520 (Spain)	+33 1 72 11 00 03 (France)
+351 30880 4750 (Portugal)	+49 69 222 25285 1 (Germany)
+46 8 566 42573 (Sweden)	+47 2103 4452 (Norway)
+45 8988 2286 (Denmark)	+358 9 7479 0199 (Finland)
+39 02 3604 2884 (Italy)	+48 22 307 3690 (Poland)
+31 10 713 8195 (The Netherlands)	+420 228 882 830 (Czechoslovakia)
+30 21 1198 3182 (Greece)	+90 212 375 5231 (Turkey)
+1 866 928 0789, +1 215 207 0061, +1 202 464 2554 (United States and Canada)	
+52 55 5004 8763 (Mexico)	+55 11 3197 5891 (Brazil)
	+56 2 2582 9336 (Chile)
+44 1235 239671 (Middle East / Africa)	+973 1619 8321 (Middle East / Bahrain)
+27 21 300 2732 (Africa / South Africa)	007 803 011 0293 (East / Southeast Asia)
+65 3158 1074 (Indonesia)	001 800 120 666 751 (Thailand)
+65 3158 1203 (Philippines)	+60 3 6207 4347 (Malaysia)
+86 512 8090 3042 (China and Taiwan)	+886 2 8793 3212 (Taiwan)

Product name : **PETRELAB® 550-Q**
 Code: **77767**

Date of issue: 21/12/2018
 Version: 4

+86 532 8388 9090 (Mainland China)	+91 11 6641 1405 (India)
+65 3158 1329 (Pakistan)	+65 3158 1195 (Sri Lanka)
+65 3158 1285 (Korea)	+82 2 3479 8401 (South Korea)
+84 8 4458 2388 (Vietnam)	+81 3 4578 9341 (Japan)
+61 2 8014 4558 (Australia)	+64 9 929 1483 (New Zealand)

Information limitations : 24/7

Section 2. Hazard identification

Classification of the substance or mixture : ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H304 - May be fatal if swallowed and enters airways.

Precautionary statements

Prevention : Not applicable.

Response : P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Section 3. Composition/information on ingredients

Substance/mixture : Substance

Chemical name : Benzene, C10-13-alkyl derivs.

Other means of identification : Linear alkylbenzene containing side alkyl chains of 10-12 carbon atoms, averaging 11.2 atoms.

CAS number/other identifiers

CAS number : 67774-74-7

Ingredient name	% (w/w)	CAS number
Benzene, C10-13-alkyl derivs.	100	67774-74-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Section 4. First-aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : No specific data.

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

- Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: Chemical splash goggles. Pursuant to EN-166:01 standard.

Skin protection

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Chemical-resistant protective suit. Wear protective gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Chemical-proof safety boots without holes for shoestrings.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: If ventilation is inadequate, use respirator that will protect against organic vapor and dust/mist.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Colorless.
- Odor** : Odorless.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting/freezing point** : <-39°C (<-38,2°F)
- Boiling point** : 239,9 to 314,1°C (463,8 to 597,4°F)
- Flash point** : Closed cup: 140 to 145,5°C (284 to 293,9°F) [Pensky-Martens.]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : 0,0013 kPa (0,0097 mm Hg) [room temperature]
- Vapor density** : 8,1 [Air = 1]
- Relative density** : 0,858 to 0,865
- Density** : 0,8562 g/cm³ [20°C (68°F)]
- Solubility** : Insoluble in the following materials: cold water and hot water.
- Solubility in water** : Not available.
- Partition coefficient: n-octanol/water** : 6,4
- Auto-ignition temperature** : 229°C (444,2°F)
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (room temperature): 0,0685 cm²/s (6,85 cSt) [ASTM D 445]
Kinematic (40°C (104°F)): 0,0423 cm²/s (4,23 cSt) [ASTM D 445]
- Flow time (ISO 2431)** : Not available.

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, C10-13-alkyl derivs.	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary : Very low toxicity to humans or animals.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Benzene, C10-13-alkyl derivs.	Skin - Moderate irritant	Rabbit	-	4 hours	-
	Eyes - Edema of the conjunctivae	Rabbit	0	-	-

Conclusion/Summary

Eyes : No.

Sensitization

Product/ingredient name	Route of exposure	Species	Result
Benzene, C10-13-alkyl derivs.	skin	Guinea pig	Not sensitizing

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Benzene, C10-13-alkyl derivs.	471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria	Negative
	476 <i>In vitro</i> Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal Cell: Germ	Negative

Conclusion/Summary : Not mutagenic in a standard battery of genetic toxicological tests.

Carcinogenicity

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Not available.

Conclusion/Summary : No additional remark.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Benzene, C10-13-alkyl derivs.	Negative	Negative	Negative	Rat	Oral	-

Conclusion/Summary : No known significant effects or critical hazards.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, C10-13-alkyl derivs.	Negative - Oral	Rat	-	-

Conclusion/Summary : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Benzene, C10-13-alkyl derivs.	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : No known significant effects or critical hazards.
Ingestion : May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Product name : **PETRELAB® 550-Q**
 Code: **77767**

Date of issue: 21/12/2018
 Version: 4

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Benzene, C10-13-alkyl derivs.	Sub-acute LOAEL Oral	Rat - Male, Female	2500 mg/kg	28 days
	Chronic NOAEL Oral	Rat	50 mg/kg	105 days
	Chronic LOAEL Oral	Rat	500 mg/kg	105 days

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Benzene, C10-13-alkyl derivs.	Acute EC50 >0,1 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute EC50 >0,041 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute NOEC 10 mg/m ³ Fresh water	Fish - Danio rerio	48 hours

Conclusion/Summary : No known significant effects or critical hazards.

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Benzene, C10-13-alkyl derivs.	301F Ready Biodegradability - Manometric Respirometry Test	64,1 % - Readily - 28 days	-	-

Conclusion/Summary : The sodium sulfonate obtained by neutralizing Petrelab 550 meets the requirements stipulated in biodegradability Detergents Regulation EC No 648/2004.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Benzene, C10-13-alkyl derivs.	-	-	Readily

Bioaccumulative potential

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Product/ingredient name	LogP _{ow}	BCF	Potential
Benzene, C10-13-alkyl derivs.	6,4	35	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : 22000

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	TDG Classification	DOT Classification	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Transport in bulk according to Annex II of MARPOL and the IBC Code **Proper shipping name** : Alkyl (C9+)benzenes
Ship type : 3
Pollution category : Y

Section 15. Regulatory information

Canadian lists

Canadian NPRI : This material is not listed.

CEPA Toxic substances : This material is not listed.

Canada inventory : This material is listed or exempted.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : This material is listed or exempted.

China : This material is listed or exempted.

Europe : This material is listed or exempted.

Japan : **Japan inventory (ENCS)**: Not determined.
Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

New Zealand : This material is listed or exempted.

Philippines : This material is listed or exempted.

Republic of Korea : This material is listed or exempted.

Taiwan : This material is listed or exempted.

Turkey : This material is listed or exempted.

United States : This material is listed or exempted.

Section 16. Other information

History

Date of printing : 21/12/2018

Date of issue/Date of revision : 21/12/2018

Version : 4

Date of previous issue : 04/12/2017

Product name : **PETRELAB® 550-Q**
Code: **77767**

Date of issue: 21/12/2018
Version: 4

Key to abbreviations

- : ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- UN = United Nations
- HPR = Hazardous Products Regulations

Procedure used to derive the classification

Classification	Justification
ASPIRATION HAZARD - Category 1	Expert judgment

References : Not available.

 Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.